

Stainless pallet truck - hygienic pallet transport

Optimum hygiene - with a stainless pallet truck the risk of bacterial contamination is minimised. The stainless products were developed in cooperation with a Creamery for use in environments where the hygiene demands are severe and where the truck is exposed to an aggressive environment and thorough cleaning.

The design prevents industrial injuries and strain on the user - focus is put on safety and ergonomic working conditions of the user. The ergonomically correct shape of the handle ensures a relaxed hold for the user.





Technical Specifications

The stainless pallet truck is available in a stainless-plus and a stainless-semi version

- RF-PLUS: 100% stainless truck
- RF-SEMI: Galvanised truck with stainless fork chassis, handle and wheel forks

Easy to clean and optimum resistance

- acid-resistant, sandblasted and electric polished fork chassis
- strong surface
- corrosion resistant

Long operating life and low maintenance

- strong construction
- AISI316L steel used on the fork chassis





RF-PLUS - for the food industry and the pharmaceutical industry with strict hygiene and sanitation requirements.



Completely open or completely closed truck elements facilitate efficient cleaning.




Closed forks mean easy cleaning and few hiding places for bacteria.




The pallet truck is also available in an explosion proof version.

Product (measured in mm)		GL 2071RF-PLUS	GL 2081RF-PLUS	GL 2081RF-SEMI
Capacity in kg		2000		2000
Lifting height	h ₃	190	200	200
Fork length	- 1	810, 970, 1140, 1220		810, 970, 1140, 1220, 1520
Overall height	h ₁	530		530
Fork span	b ₅	520, 680		520, 680
Length without forks	l ₂	340		340
Overall length	11	1480		1480
Fork width	е	160		160
Wheelbase	у	1170		1170
Overall height	h ₁₄	1220		1220
Lowered height	h ₁₃	75*	85	85
Load centre	С	1/2		1/2
Ground clearance	m ₂	28	38	38
Turning angle of the wheels		230°		230°
Fork wheels - single		Ø70 x 90	Ø80 x 90	Ø80 x 90
Fork wheels - tandem			Ø80 x 70	Ø80 x 70
Steering wheel		Ø180 x 50	Ø200 x 50	Ø200 x 50
Weight		68 kg (520 x 1140)		

^{*} Holes in the forks for the wheel holder







RF-SEMI - for the food industry in areas, where hygiene demands are not so high, but corrosion resistance important.



Ergonomic handle ensures the



RF-PLUS pallet truck being used



Wheels with rubber-sealed

Please ask for specification details or visit our website www.logitrans.com. We also offer tailor-made solutions.

